

# NEW COMBUSTIBLE GAS LEAK DETECTOR NEW CD100A

## CD100A

The CD100A is designed to detect combustible gas leaks in residential and small commercial applications. It is small, easy to use and has a 18" long flexible gooseneck for hard to reach areas.

- Simple adjustable tick rate increases as the sensor tip approaches a leak
- Audio and visual tick rate, fully adjustable
- Easy one hand operation
- Long 18" (45cm) gooseneck for hard to reach areas
- 'Tip light' in sensor cover illuminates the area of the leak
- Rubber boot protects instrument
- Sensor provides accurate detection
- Headphone jack
- Separate battery compartment for quick and easy battery replacement

### Partial list of gases sensed:

Acetone, Alcohol, Ammonia, Benzene, Butane, Gasoline, Halon, Hydrogen Sulfide, Industrial Solvents, Jet Fuel, Laquer Thinners, Methane, Naphta, Natural Gas, Propane, Refrigerants, Toluene ... and more



## SPECIFICATIONS

Power Supply	9V Alkaline battery
Battery life	5 hours typical use
Sensor	Solid state semiconductor
Sensitivity	50 ppm
Dimensions	8" x 4" x 1.5" (200x100x38 mm)
Gooseneck	18" (450mm)
Tick adjustment	Fully adjustable thumbwheel
Tick indication	Flashing LED

## ACCESSORIES

Replacement Sensor
Replacement Sensor Cap
Headphones
Hard Carrying Case